

Main specification

Item code	DAI 0101
Temperature range (°C)	-30 / -60
Max. ambient temperature (°C)	25
Capacity (L)	71
Exterior dimensions WxDxH (mm)	552x648x850
Interior dimensions WxDxH (mm)	390x390x465
Weight (kg)	53
Insulation (mm)	80
Cooling technology	static
Controller model / probe type	Dixell XR30CX / PT1000
Power supply (V)	230
Frequency (Hz)	50
Power consumption (KWH/24H)	5,1
AMP (A)	2,0
Power (Watt)	297
Horse Power (HP)	1/2

Other features

Automatic defrost	no
Antifreeze function	no
Vacuum release port	no
Access port for external probe etc. (Int. diameter mm)	12
Light	no
Lock with key	yes
Castors (total pcs) / castors with brake (pcs)	4 / optional
Fixed feet (pcs) / levelling feet (pcs)	no
Sub lids / sub doors (qty)	no
Reversible doors (qty)	no
Shelf	no
Drawer	no
Basket	yes
Max. no. of baskets (pcs)	2
Max. load per basket (kg)	11
Total capacity of 50mm boxes 9x9 dividers (pcs)	40
Total capacity of 75mm boxes 9x9 dividers (pcs)	25
Total capacity of 96mm boxes 9x9 dividers (pcs)	20

Display / Data / Alarm

Alarm display as text (not codes)	no
Visual / acoustic alarm	yes / yes
Power failure alarm	no
Ajustable high / low temperature alarm	yes / yes
Open door alarm	no
Probe failure alarm	yes
Low battery alarm	no
Compressor failure alarm	no
Battery backup for alarms (approx. hrs.)	no
Voltage free contact for remote alarm (e.g. GSM alarm module)	yes
Electronic data logger	no
RS 485 port	no
USB port for software update & data download	no
Temperature chart recorder	optional
Display type	LED display
Number of optional reference probes	no
Password protection for turning unit on/off	no
Temperature graph on display	no

Refrigeration & Cabinet

Number of compressors	1
Refrigerant	nature R
Interior cabinet material	prepainted steel
Exterior cabinet material	prepainted steel
Colour (exterior cabinet)	white
Foam type	polyurethane
VIP vacuum insulated panels	no

Shipping

Shipping weight (kg)	76
Shipping dimensions (cm)	68x64x116
Shipping volume (m ³)	0,51

Documentation (downloads)

Product datasheet	Available on website
Dimension drawing	Available on website
Wiring diagram	Available on website
CE-Certificate	Available on website
IQ/OQ	Available on website
Operating instructions	Available on website

Accessories

ARCTIKO GSM Alarm Module®	Add-on
ARCTIKO Cryo Gloves®	Add-on
ARCTIKO Voltage Stabilizers®	Add-on
ARCTIKO Voltage Converters®	Add-on
ARCTIKO Temperature Chart Recorder®	Add-on

Racks & Boxes

Rack Model	Box size (height mm)	Rack model & total quantity	No. of boxes per rack (depth x height)	Total no. of boxes	Exterior dimensions of rack (wxdxh mm)
Chest front racks	32	5 x CFR34-12	12	60	138 x 138 x 438
Chest front racks	40	5 x CFR40-10	10	50	138 x 138 x 426
Chest front racks	50	5 x CFR50-08	8	40	140 x 140 x 441
Chest front racks	75	5 x CFR75-05	5	25	140 x 141 x 400
Chest front racks	80	5 x CFR80-05	5	25	138 x 138 x 416
Chest front racks	90/96/100	5 x CFR100-04	4	20	140 x 141 x 421